



PDF

Download PDF

530

KRAFT UTILITY PAPER FLATBACK TAPE

DESCRIPTION


Pressure sensitive flatback with an aggressive blend of solvent cast natural/synthetic rubber adhesive designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. Performs well under a wide range of temperature and humidity conditions. 530 is designed for use in applications where reduced weight can provide packaging material savings. Complies with Postal Regulation for Unsecured Packages. Product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beaming/leaving, splicing, and taping.

ENVIRONMENTAL COMPLIANCE

PDP-T-42C, Type II
C.I.D. A-A-883B, Type II

 intertape polymer group

100 Paramount Drive, Suite 300 (Stevens, NJ, 07832) USA
Customer Service: 800-PG-8271 (800 474 8271)
Paper Technical Service: 877-447-4932
www.intape.com | info@intape.com

While we strive to deliver the highest quality products and services, we cannot be held responsible for any damage or loss of materials or equipment caused by the use of our products. Intertape Polymer Group, Inc. and its subsidiaries, affiliates, and agents, disclaim any liability for damage or loss of materials or equipment caused by the use of our products. Intertape Polymer Group, Inc. and its subsidiaries, affiliates, and agents, disclaim any liability for damage or loss of materials or equipment caused by the use of our products. Intertape Polymer Group, Inc. and its subsidiaries, affiliates, and agents, disclaim any liability for damage or loss of materials or equipment caused by the use of our products.


EFFECTIVE DATE:

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Kraft Flatback
Adhesive	Solvent Cast Natural / Synthetic Rubber
Adhesion to Steel (pairs of width): PSTC-101	58 (15.9 N/25mm)
Tensile Strength (pairs of width): PSTC-111	40 (175 N/25mm)
Displacement (% at break)	7
Total Thickness (mil): PSTC-113	7.3 (Ø 16mm)
Operating Temperature Range	
Operating	+20°F → +175°F (4.4°C → +79°C)
Color	Brown



5

PDF

Download PDF

PM2

TAN MEDIUM GRADE PAPER FLATBACK TAPE

DESCRIPTION


A quick, easy sealing, economical, pressure-sensitive flatback tape which can increase packaging line efficiency. PM2 offers a positive attractive seal and excellent adhesion to discourage pilfering. Performs well under a wide range of temperatures through a wide range of humidity conditions. Offers the advantages of a balance of high quick stick and excellent holding properties. Performs well as a low temperature taping tape and meets USPS requirements. Product is not repulpable.

PRODUCT APPLICATIONS

Can be used on all types of cartons.

GOVERNMENT COMPLIANCE

ASTM D6123, Type II
PPP-T-42C, Type II
C.I.D. A-A-883B Type II
Sealing SAC 9317

 intertape polymer group

100 Paramount Drive, Suite 300 (Stevens, NJ, 07832) USA
Customer Service: 800-PG-8271 (800 474 8271)
Paper Technical Service: 877-447-4932
www.intape.com | info@intape.com

While we strive to deliver the highest quality products and services, we cannot be held responsible for any damage or loss of materials or equipment caused by the use of our products. Intertape Polymer Group, Inc. and its subsidiaries, affiliates, and agents, disclaim any liability for damage or loss of materials or equipment caused by the use of our products. Intertape Polymer Group, Inc. and its subsidiaries, affiliates, and agents, disclaim any liability for damage or loss of materials or equipment caused by the use of our products. Intertape Polymer Group, Inc. and its subsidiaries, affiliates, and agents, disclaim any liability for damage or loss of materials or equipment caused by the use of our products.


EFFECTIVE DATE:

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Kraft Flatback
Adhesive	Natural Rubber / Resin
Adhesion to Steel (pairs of width): PSTC-101	57 (15.6 N/25mm)
Tensile Strength (pairs of width): PSTC-111	36 (157.6 N/25mm)
Displacement (% at break)	3
Total Thickness (mil): PSTC-113	9 (Ø 15mm)
Operating Temperature Range	
Operating	+20°F → 225°F (+4°C → +107°C)
Color	Tan



- Adhesion to SST: 57 oz/in.
- Tensile strength: 37 lbs/in width.
- Elongation: 4%.
- Range temperature application 40F to 225F.
- Meets MIL Spec D6123, Type II.
- 3" neutral paper core.

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.