



Product Data Sheet

Striped Safety Warning Tape (Safety Stripe?Tape 66X40)

Safety Stripe?Tape conformable Soft PVC Vinyl. Synthetic Rubber Adhesive, self-extinguishing.

- Adhesion: 13.7 oz/in.
- Tensile strength: 15 lbs/in.
- Elongation: 210% at break.
- Temperature resistance: 14°F to 176°F.

Will not corrode copper, brass, steel, or aluminum. Safety Stripe?Tape used for striping & warning, marking of hazardous areas and exits to comply with OSHA requirements per paragraph 1910.144 of the Federal Register.

3? neutral paper core.

Uses:

Colors	Typical Uses
Black/Yellow ?	Physical Hazard/Caution
Red/White ?	Fire Equipment/First Aid
Black/White ?	Traffic/Housekeeping
Green/White ?	Decorative Identification
Magenta/Yellow ?	Radiation Hazard

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.