



Product Data Sheet

Contractors Grade Duct Tape (67270)

High tensile Polyethylene-coated cloth with a natural rubber and a synthetic resin adhesive. It is superior performance duct tape specially designed for the high demand contractor applications. Best Duct Tape with excellent shear values to surface and backing. It has a good conformability and excellent resistance to tear.

3" neutral core/carton. 11.8 mil, 63 mesh.

Used in HVAC industry to provide an excellent seal for thermal insulation and air conditioning ducts, used as a moisture barrier for both indoor and outdoor applications. Also used in asbestos abatement applications; as a quality waterproof packaging tape for export shipments; for splicing, vinyl repair, protecting and bundling.

- Adhesion to steel: 39 oz/in. roll unwind.
- Tensile strength: 31 lbs/in.
- Elongation at break: 12%.
- Temperature range: -31°F to 176 degrees F.

4 COLORS AVAILABLE: Silver (Gray), Black, White, Olive Drab.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

tapedepot.com | support@tapedepot.com | 888.282.8273

2023-03-30 07:09:11 172.31.87.187