



## Product Data Sheet

### 8.5 mil Uni-directional Filament

330# Tensile.

Very high strength polyester backed unidirectional fiberglass filament reinforced tape coated with an aggressive and high shear resistant clear natural rubber resin adhesive. Its high tensile strength and high adhesion to a variety of surfaces make this product suitable for HIGH DEMAND bundling and strength reinforcing applications.

- Adhesion to steel: 40 oz/in.
- Elongation: 4.5%.
- Industrial grade filament tape for strapping, bundling and palletizing.
- 3? neutral core.
- MIL spec: ASTM-D-5330 type II and PPP-T-97E, type II Class B.

58.5? (1486mm) x 1551m (1697 yds) Jumbos available.

Alternative to Tesa #53311, IPG #RG16, Cantech #188-00; Permacel P-167 & P-247; Shurtape #GS531; 3M #880NR, #893 & #898.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-04-26 09:44:38 172.31.87.187