



Product Data Sheet

Carton Sealing Tape Acrylic Solvent Based Adhesive (36XX)

Polypropylene Carton Sealing Tap, ACRYLIC SOLVENT BASED ADHESIVE

3622 - Clear & Tan

- 2.2 mil (0.055mm). 28 micron film. A biaxially oriented polypropylene tape, coated with a Solvent Based Acrylic Adhesive.
- Adhesion: 23 oz/in.
- Tensile: 20 lbs/in.
- Elongation at break: 140%.
- Temp. resistance: 35°F to 150°F. 3? neutral core/carton.
- 49? (1260mm) x 4000M Length Jumbo Rolls

3626 - Clear & Tan

- 2.7 mil (0.068mm). 40 micron film. A biaxially oriented polypropylene tape, coated with a Solvent Based Acrylic Adhesive
- Adhesion: 27 oz/in.
- Tensile: 24 lbs/in.
- Elongation at break: 140%.
- Temp. resistance: 35°F to 150°F.
- Great balance of adhesion and tensile strength for heavy weight carton sealing applications. 3? neutral core/carton. Meets SPEC. A-A-1684C.

3634 - Clear & Tan

- 3.6 mil (0.09mm). 60 micron film. A biaxially oriented polypropylene tape, coated with a PREMIUM GRADE Solvent Based Acrylic Adhesive.
- Adhesion: 33 oz/in.

NOTE: All properties listed above are typical test results obtained from a series of laboratory tests and should not be used for product writing specifications. Before using this product, user shall determine the suitability of the product for their application. User assumes all risks and liabilities in connection therewith. All test results are based on standard test methods and high tensile strength makes it an excellent choice for extremely demanding packaging needs. 3? neutral core/carton.

tapedepot.com | support@tapedepot.com | 888.282.8273