



Product Data Sheet

Carton Sealing Tape Natural Rubber Adhesive (3418)

Polypropylene Carton Sealing Tape.

Excellent Cold Room and Refrigerated Packing Tape. Instantly grips to recycled, used or rough surface corrugated cardboard.

NATURAL RUBBER BASED ADHESIVE (recommended for recycled cartons and cold temperature application)

3418 Specs

- 1.80 mil (0.045mm). 25 micron film. Solvent Based Natural Rubber Adhesive.
- Tensile: 21 lbs/in.
- Adhesion to steel: 22 oz/in.
- Elongation: 170%.
- Application temperature range: 0°F to 150°F.
- 3? neutral core.

3420?Specs

- 2.0 mil (0.048mm). 28 micron film. Solvent Based Natural Rubber Adhesive.
- Tensile: 23 lbs/in.
- Adhesion to steel: 22 oz/in.
- Elongation: 170%.
- Application temperature range: 0°F to 150°F.
- 3? neutral core.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith.

All test procedures used are in accordance with ASTM and PSTC methods.

3426?Specs

- 2.5 mil (0.062mm), 40 micron film.?Solvent Based Natural Rubber Adhesive.
- Tensile: 30 lbs/in.
- Adhesion to steel: 20 oz/in.
- Elongation: 190%.
- Application temperature range: 0°F to 150°F.
- 3? neutral core

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.