



# Product Data Sheet

## Colored Electrical Tape 3/4 in - 10 Pack (62018d)

**3/4 inch Colored Electrical Tape, 10 Pack. Each roll is 66 feet long.**

ALL WEATHER COLORED ELECTRICAL TAPE Flame Retardant & Cold Resistant

Our 10 Pack of Colored Electrical Tape (62018D) is a colored PVC Electrical Insulation Tapes with Rubber based adhesive, which is flame retardant and cold weather resistant. Used generally for insulating, protection, and color-coding of electrical wires; and for wire harnessing in the automotive industry.

Every household should have at least a few rolls of 3/4" electrical tape, often the [black 3/4"](#) is ideal because of its low cost, handiness, and ease of access.

This colored version of our electrical tape, are used by professional electricians, artists, and anyone else looking to have a variety of color in their tape. The 10 pack mixed multipack makes it more affordable than our [10 pack or 100 pack of single color electrical tape](#).

Colors: Yellow, Green, Orange, Purple, White, Red, Blue, Gray, Black, Pink.

62018d Rolls are individually cello-wrapped and labeled, and custom slit and bulked packed. 1-1/2" (38.1MM) UL/CSA Labeled Core.

### SPECIFICATIONS:

- Backing: Plasticized PVC
- Adhesive: Rubber based
- Total Thickness: 7 mil (0.18mm)
- Voltage Breakdown: 8kv

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith.

All test procedures used are in accordance with ASTM and PSTC methods.

**[tapedepot.com](http://tapedepot.com) | [support@tapedepot.com](mailto:support@tapedepot.com) | 888.282.8273**

2021-09-27 06:55:28 172.31.87.187

- Peel Adhesion: 16.4 oz/in
- Tensile Strength: 14.8 lbs/inch
- Elongation at Break: 200%
- Temperature Resistance: 14°F to 176°F
- Core listed: UL/CSA/CE

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**[tapedepot.com](http://tapedepot.com) | [support@tapedepot.com](mailto:support@tapedepot.com) | 888.282.8273**

2021-09-27 06:55:28 172.31.87.187