

# Product Data Sheet

Custom Printed Non-Reinforced (Hand Tearable) Paper Tape

Non-reinforced paper tape manufactured with water-activated adhesive.

## PRODUCT APPLICATION

Recommended for inner carton sealing or for lightweight cartons that will be shipped in unitized loads or full pallets.

This product is also recommended for more aesthetic uses such as a final branded seal or wrapper that adds texture, branding and isn't a burden for your customer's to remove.

## CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Paper:

57 lb (93 g/m<sup>2</sup>)

Natural Kraft Paper Water-Activated Adhesive: 15 lb (24 g/m<sup>2</sup>)

Waxy Maize Starch Based Adhesive, Designated as #410 Total Basis Weight: 72 lb (117 g/m<sup>2</sup>)

PHYSICAL PROPERTIES: Caliper 5.6 mils (0.14mm)

MD Tensile 45 lbs/in (197 N/25mm)

CD Tensile 23 lbs/in (101 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

Fipago:

2/0 23

2/1 42

5/0 48

15/0 82

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-05-09 05:53:15 172.31.87.187