

# Product Data Sheet

Double Coated Heavy-duty Scrim Tape.

A 9.1 mils thick polyester (PES/PVA) reinforced transfer tape with an aggressive, modified solvent free water based acrylic adhesive. Gold 90 gr. siliconized paper release liner. The adhesive system is extremely aggressive, and will bond well to nearly all materials; even to difficult surfaces like foam, PE and PP films. It has good temperature, UV, aging, and water vapor resistance. Used for permanent bonding of plastic, metal and wood (P.M.W.) surfaces. APEO/APE Free. Primarily designed for use in bonding carpet and plastic baseboard molding to walls, ceilings, modular units, etc. Backing: PES/PVA Scrim.

\* Adhesion: 109.6 oz./in.

\* Adhesive Weight: 220 gr/m<sup>2</sup>.

\* Temperature Resistance: -40°F to 203°F.

\* 3" neutral core/carton.

54" (1371mm) x 800M Master Jumbo Rolls Available.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-04-18 00:00:07 172.31.87.187