



Product Data Sheet

Double Coated Polyester Tape 3.4 Mil - Clear (51114)

Double Coated Polyester Tape 3.4 mil (0.086mm) exclusive of liner. 0.4 mil thin clear polyester film coated with an aggressive synthetic hot melt rubber adhesive and wound on a 2.7 mil (82 gr.) white siliconized paper release liner. Superior moisture resistance in humid conditions once bonded. Excellent quick-stick, with moderate temperature resistance. Not recommended for use in applications at temperatures above 158°F. Perfect for splicing of papers, plastics, films, foils, etc. Used in general purpose bonding, mounting and laminating applications (i.e. nameplates, mouse pad assembly).

- Adhesion: 120 oz/in.
- Elongation: 130%.
- Environmentally friendly; solventless adhesive; ROHS compliant.
- Temperature range: -14°F to 158°F. 3" neutral core/carton.
- Color: Polyester Clear

Also known as: Adchem #3175M; Venture #512; Scapa #S-662.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

tapedepot.com | support@tapedepot.com | 888.282.8273

2024-04-17 02:37:43 172.31.87.187