

# Product Data Sheet

## Double Coated Polyester 3.5 Mil - Bright Red (54109R)

### Red Double Sided Polyester Tape 3.5 Mil (54109R)

Red Double Sided Polyester Tape 3.5 mil (0.089mm) exclusive of liner. 0.5 mil bright red, Polyester (opaque) film coated on both sides with an aggressive, clear acrylic pressure sensitive adhesive. High tack/adhesion/shear strength, excellent temperature performance. For splicing paper, plastics, films, foils, low/high energy surfaces and other continuous web processes when a visual splice is critical.

- \* Peel adhesion: 95 oz/in.
- \* Tensile: 7.5 lbs/in.
- \* Elongation: 100%.
- \* Temperature resistance: -40°F to 225°F (175°F for continuous load).
- \* 55# Kraft paper liner.
- \* 3" neutral core/carton.

56" (1422mm) x 1200M Master Jumbo rolls available

Alternative to Venture #515R; 3M #9420 & #9737R; Berry Plastics #756; Int'l Tape #713R; Scapa #5234R; Newbond #TF2404.

---

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.