



## Product Data Sheet

Free Shipping

on this product!

Double Coated Polyester (Clear) – Red PP Liner\*

7.6 mil exclusive of liner. 0.5 mil clear polyester film coated with a very aggressive, high tack, high shear solvent based acrylic adhesive. This product comes with a dimensionally stable Red PP release liner making it suitable for precision die-cut applications. It has excellent temperature, UV, aging, and water vapor resistance. Also has good plasticizer resistance.

- \* Adhesion to SST: (1 min. dwell): 88 oz/in.
- \* Temperature resistance: up to 320°F long term, 356°F short term.
- \* Elongation: 50%.
- \* Tensile strength: 9.3 lbs/in.
- \* Used for bonding, joining, laminating when high tack and high shear are critical.
- \* 3" neutral core/carton.

Alternative to Tesa #4965, Lohman #373.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-04-27 01:39:04 172.31.87.187