



## Product Data Sheet

### Double Coated Polypropylene/Polyolefin Tape (Clear)

3.8 mil (0.097mm) exclusive of liner. 1.0 mil clear BOPP film. Synthetic hot melt rubber adhesive. 2.8 mil Gold siliconized paper release liner. Used for core start-ups, splicing, holding, joining, attaching, mounting, and laminating applications. Good tack on flat surfaces. Peel Adhesion: 73.1 oz/in. Tensile: 23 lbs/in.

- Elongation: 165%. Performing temperature: 14°F to 122°F.
- Temperature application: -4°F to 149°F short term.
- 3" neutral core/carton.
- 53.5" (1360mm) x 1200M Master Jumbo Rolls Available.

*Alternative to Tesa #64621; Venture #1162 & #1163; Sicad #700RdA; Davik #dS4101; Boma #4140; 3M #9576.*

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-03-29 10:53:24 172.31.87.187