

Product Data Sheet

Double Coated White PVC Tape 9.0 mil (54420)

9.0 mil exclusive of liner. 1.5 mil White PVC Tape film coated on both sides with a solvent based Acrylic Adhesive. Gold siliconized paper liner. The adhesive system of this double coated tape is aggressive, and will bond well to nearly all materials; even to difficult surfaces like foams, PE and PP films. It has excellent temperature, UV, aging, and water vapor resistance.

Applications

Used for bonding rubber, plastic, metal and wood substrates; for permanent mounting of nameplates and decorative trim on appliances and furniture.

Physical Properties...

- * Adhesion to SST 110 oz/in.
- * Elongation 35%
- * Minimum Application Temp: 15°C (59°F)
- * Temperature resistance -40°F to 158°F continuous
- * Alternative to Tesa #4970; Scapa #S301; #3M #419; IPG #597; Lohman #370.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

tapedepot.com | support@tapedepot.com | 888.282.8273

2023-03-30 07:20:15 172.31.87.187