



## Product Data Sheet

### Aluminum Foil Tape 2 Mil - Self Wound without Liner

Foil Tape is a 2 mil self-wound dead soft malleable Aluminum Foil coated with acrylic adhesive. Malleable foil conforms well to irregular surfaces. Excellent harness wrap tape. Designed for non-critical applications such as sealing out dust and moisture, masking and duct sealing. Can be used for heat reflection in the appliance industry and as a mask for electroplating. This linerless product saves time and labor in stripping of release liner and produces less waste.

#### Physical Properties:

- Total tape thickness ? 3.3 mil
- Adhesion to steel ? 50 oz/in
- Elongation ? 3.5%
- Tensile strength ? 17 lbs/in
- Temperature range ? -40°F to 350°F
- 3? neutral core

*Alternative to 3M #431; Lamart #520SW; Venture #807-2 & #2520CW*

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-04-19 11:22:36 172.31.87.187