



Product Data Sheet

High Performance Acrylic Adhesive Foil Tape 5 Mil (45050)

Acrylic Adhesive Foil Tape – 5 mil high strength Aluminum Foil backing, combined with a high performance solvent acrylic adhesive, protected by an easy-release silicone release paper. Perfect for joining and sealing Foil-Scrim-Kraft facing laminate fiberglass blanket/duct board joints and seams. May also be used for industrial uses.

Physical Properties:

Total tape thickness ? 6.8 mil

Rolling Tack (11mm ball) ? <8.0 in

Peel adhesion ? 65 oz/in

Holding Power ? 1,200 Min

Temperature range ? -4°F to 230°F

3? neutral core

Alternative to 3M #427; Permacel #P14; Arclad #S-5795; Ideal #489; Scapa #P178; St. Gobain #A662; Polyken #347.

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

If you need assistance when ordering: Call Us at (877) 284-4781.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

tapedepot.com | support@tapedepot.com | 888.282.8273

2024-04-26 16:56:43 172.31.87.187