∧lanson

Product Data Sheet

General Purpose Aluminum Tape (4X0XXRA)

Aluminum Tape (with liner) – Acrylic Adhesive.? Economical aluminum foil tape for moderate demand applications. 1.2 mil dead soft aluminum foil, coated with a solvent based acrylic adhesive; removable paper release liner. Malleable foil conforms well to irregular surfaces. Used for vapor barrier protection, waterproof sealing, heat reflection, and dissipation, masking in paint stripping and electroplating.

Physical Properties:

Total tape thickness: 2.8 mil

• Elongation: 3%

Peel adhesion: 72 oz/in

Tensile: 11 lb/in3" neutral core

Other roll widths available upon request.

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, the user shall determine the suitability of the product for his/her use; and the user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.