## **∧**lanson

## **Product Data Sheet**

## **General Purpose Masking Tape - Intertape#513**

Beige crepe paper masking tape coated with an aggressive pressure-sensitive natural rubber adhesive. Designed primarily as an all-purpose product for non-critical applications.

**Product Application** 

Masking Tape for painting, textile, carpet seaming, silk screening, mail rooms, golf club shaft (buildup), school bids, and for light-duty bundling, packaging, industrial, manufacturing, splicing and tabbing.

Government Compliance

Product qualified to meet ASTM 06123 specifications.

Nominal Values

\* Backing: Crepe Paper

\* Adhesive: Natural/Synthetic Rubber

\* Adhesion to Steel (oz./in. width): 36 (9.8 N/25 mm)

PSTC-1

\* Tensile Strength (lbs/in. width): 19 (83.2 N/25mm)

PSTC-31

\* Elongation (at break): 6.4%

PSTC-31

\* Total Thickness(mils): 5.0 (0.127mm)

PSTC-33

\* Quick Stick to Steel oz/in. width): 12 (3.3 N/25mm)

PSTC-5

\* Temperature Resistance? 50?F ~ 180?F ( 10?C ~ 82?C)

\* Color: Beige
NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.