



PDF

Download PDF

530

KRAFT UTILITY PAPER  
FLATBACK TAPE

DESCRIPTION

Pressure sensitive flatback with an aggressive blend of solvent cast natural/synthetic rubber adhesive designed to offer a positive, adhesive seal and excellent adhesion to minimize carrier, sealing failures and prevent pilferage. Performs well under a wide range of temperature and humidity conditions. 530 is designed for use in applications where reduced weight can provide packaging material savings. Complies with Postal Regulation for Unrestricted Packages. Product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beamforming, sealing, and labeling.

ENVIRONMENTAL COMPLIANCE

PPP-T-42C, Type II  
C.I.D. A-A-583B, Type II

INTERTAPE POLYMER GROUP®  
TECHNICAL DATA SHEET

NORMAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Kraft Flatback
<b>Adhesive</b>	Solvent Cast Natural / Synthetic Rubber
<b>Adhesion to Steel</b> (pair of wheels) PSTC-101	58 (15.9 N/25mm)
<b>Tensile Strength</b> (pair of wheels) PSTC-131	40 (175 N/25mm)
<b>Displacement</b> (in air break)	7
<b>Total Thickness</b> (mil) PSTC-135	7.3 (0.16mm)
<b>Operating Temperature Range</b>	
Operating	-40°F → +179°F (-41°C → +79°C)
<b>Color</b>	Brown

Intertape polymer group

100 Paramount Drive, Suite 300 (Berkeley, CA, 94710) USA  
Customer Service: 800-PPG-5271 / 800-474-5271  
Tape Technical Service: 877-447-4832  
www.inttape.com • info@inttape.com

While we endeavor to be as reliable as possible, the appearance and performance of our products are only for general guidance and are not warranted or guaranteed for accuracy and performance. The user must be able to determine, through actual testing, if the product meets the requirements of the application intended for its use. There is no warranty of fitness for a particular purpose. Our products are sold on condition of sale, applicable to all regions, and are provided for the convenience of our clients. Intertape Corporation, Intertape Polymer Group, Inc. and its subsidiaries and affiliates assume no liability for damages of any kind resulting from the use of our products. Intertape Corporation, Intertape Polymer Group, Inc. and its subsidiaries and affiliates assume no liability for damages of any kind resulting from the use of our products. Intertape Corporation, Intertape Polymer Group, Inc. and its subsidiaries and affiliates assume no liability for damages of any kind resulting from the use of our products.

EFFECTIVE DATE:

PDF

Download PDF

PM2

TAN MEDIUM GRADE PAPER  
FLATBACK TAPE

DESCRIPTION

A quick, easy sealing, economical, pressure-sensitive flatback tape which can increase packaging line efficiency. PM2 offers a positive attractive seal and excellent adhesion to discourage pilfering. Performs well under a wide range of temperatures through a wide range of humidity conditions. Offers the advantages of a balance of high quick stick and excellent holding properties. Performs well as a low temperature splicing tape and meets USPS requirements. Product is not repulpable.

PRODUCT APPLICATIONS

Can be used on all types of cartons.

GOVERNMENT COMPLIANCE

ASTM D6123, Type II  
PPP-T-42C, Type II  
C.I.D. A-A-583B, Type II  
Sealing SAC 5317

INTERTAPE POLYMER GROUP®  
TECHNICAL DATA SHEET

NORMAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Kraft Flatback
<b>Adhesive</b>	Natural Rubber / Resin
<b>Adhesion to Steel</b> (pair of wheels) PSTC-101	57 (15.6 N/25mm)
<b>Tensile Strength</b> (pair of wheels) PSTC-131	36 (157.6 N/25mm)
<b>Displacement</b> (in air break)	3
<b>Total Thickness</b> (mil) PSTC-135	9 (0.15mm)
<b>Operating Temperature Range</b>	
Operating	-40°F → +225°F (-41°C → +107°C)
<b>Color</b>	Tan

Intertape polymer group

100 Paramount Drive, Suite 300 (Berkeley, CA, 94710) USA  
Customer Service: 800-PPG-5271 / 800-474-5271  
Tape Technical Service: 877-447-4832  
www.inttape.com • info@inttape.com

While we endeavor to be as reliable as possible, the appearance and performance of our products are only for general guidance and are not warranted or guaranteed for accuracy and performance. The user must be able to determine, through actual testing, if the product meets the requirements of the application intended for its use. There is no warranty of fitness for a particular purpose. Our products are sold on condition of sale, applicable to all regions, and are provided for the convenience of our clients. Intertape Corporation, Intertape Polymer Group, Inc. and its subsidiaries and affiliates assume no liability for damages of any kind resulting from the use of our products. Intertape Corporation, Intertape Polymer Group, Inc. and its subsidiaries and affiliates assume no liability for damages of any kind resulting from the use of our products. Intertape Corporation, Intertape Polymer Group, Inc. and its subsidiaries and affiliates assume no liability for damages of any kind resulting from the use of our products.

EFFECTIVE DATE:

- Adhesion to SST: 57 oz/in.
- Tensile strength: 37 lbs/in width.
- Elongation: 4%.
- Range temperature application 40F to 225F.
- Meets MIL Spec D6123, Type II.
- 3" neutral paper core.

*Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.*

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.