



Product Data Sheet

Laminated Striped Safety Warning Tape (660×0)

Safety warning tape with conformable Soft PVC Vinyl. Synthetic Rubber Adhesive, self-extinguishing.

- Adhesion: 13.7 oz/in.
- Tensile strength: 15 lbs/in.
- Elongation: 210% at break.
- Temperature resistance: 14°F to 176°F.

Will not corrode copper, brass, steel, or aluminum. For striping & warning, marking of hazardous areas and exits to comply with OSHA requirements per paragraph 1910.144 of the Federal Register. 3/4" neutral paper core.

Uses:

Colors ? Typical Uses

Black/Yellow ? Physical Hazard/Caution

Red/White ? Fire Equipment/First Aid

Black/White ? Traffic/Housekeeping

Green/White ? Decorative Identification

Magenta/Yellow ? Radiation Hazard

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications.

Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

tapedepot.com | support@tapedepot.com | 888.282.8273

2024-04-17 01:19:38 172.31.87.187