



Product Data Sheet

Pipe Thread Tape, 4 Mil

Unsintered Virgin Polytetrafluoroethylene (PTFE)

Pipe Thread Tape 100% Virgin PTFE. White film in labeled plastic spool/ box. Lubricates joints, making them easy to assemble for a leak-proof seal. Mil-spec T-27730A. Country of origin: China. Meets JISK (Japan) Standards. Boxes of 1000 contain 10 cartons of 100. ISO 9001.

Physical Properties:

- Total Thickness 4.10 mil (0.105mm)
- Density 0.31 gm/cm³
- Elongation (at break) 30.0%
- Tensile Strength: 9.9 N/m²

Alternative to 3M #48 & #547.

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.