



## Product Data Sheet

### Polyethylene Tape 7 Mil Rubber 60 Yd (63507)

Polyethylene Tape has 4.5 mil Low-density polyethylene film coated with a synthetic rubber adhesive. Its tough polyethylene backing offers good abrasion and tear resistance. Low-tack adhesive suitable for surface protection applications. Excellent for low-temperature bonding. 3? paper core.

Applications: Ideal for wire identification, surface protection, seaming and splicing of films.

#### Physical Properties:

- Total Thickness ? 7.0 mil (0.178mm)
- Film Thickness ? 4.5 mil
- Adhesive ? Synthetic Rubber
- Tensile Strength ? 18 lbs/in
- Elongation ? 80%
- Peel Adhesion ? 60 oz/in
- Adhesion to Backing ? 35 oz/in

4 COLORS AVAILABLE: Clear, White, Black, Red.

Alternative to Scapa #135.

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.