



Product Data Sheet

Single Sided PVC Foam Tape - Low Density (16SLD)

Single Sided Adhesive Foam Tape - Low Density (16SLD)

Single Sided Adhesive Foam Tape has a low density (between 6-10 lbs per foot). Closed cell PVC foam tape coated on one side with a high-performance acrylic adhesive, and carried on a white siliconized paper liner. Good combination of flexibility and conformability with strength & wear resistance. Excellent weatherability and chemical resistance. It is a clean, waste-free substitute for liquid sealants. Economical single sided adhesive foam tape, general purpose foam tape. Used in applications requiring positive seals on irregular surfaces or when flexibility and conformability to seal tight radius curves are critical considerations.

Applications:

Used extensively in the automotive, HVAC, and construction industries to provide air & weather tight seals; for gasketing, cushioning, vibration control in speakers, vehicles, electronic components, door frames, etc.

Physical Properties:

- Force to compress 25% (range) 0.5-4.0 psi
- Compression deflection (range) 0.5-2.5 psi
- Tensile Strength Minimum 15 psi
- Service Temperature -40°F to 180°F

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.