



## Product Data Sheet

### Standard Grade Gaffer Tape

High-quality polyethylene coated cloth laminated to a low gloss finish film, coated with a natural rubber based adhesive. Conforms well to irregular surfaces and will not twist or curl during application. Excellent water, vapor and abrasion resistance. Clean removal on most surfaces (surface type & dwell time may affect performance). Suitable for entertainment type applications (concerts, trade shows, etc.) where minimal visibility of tape is desired. Used for holding down cables, wires, electrical cords, and in stage set-ups for marking placement (i.e. "spike" tape). Suitable as bookbinding tape for seaming & reinforcement.

**11 COLORS AVAILABLE: Black, White, Gray, Yellow, Red, Dark Blue, Blue, Dark Green, Brown, Burgundy and Olive Drab**

Peel Adhesion: 29 oz/in.

Tensile Strength: 36 lb/in.

Temperature Resistance: -31°F to 176°F.

3" neutral core/carton.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

**tapedepot.com | support@tapedepot.com | 888.282.8273**

2024-04-19 05:26:01 172.31.87.187